



Nondestructive Testing

Ultrasonic Testing of Coated Metals

High-Precision Multi-Echo Technology

SONOWALL 60 measures reliably through paint and protective layers as well as corroded surfaces. The light and precise measuring device is used to detect signs of wear and corrosion by means of multiple echo technology.

Applications

The gauge is designed for the aacurate, non-destructive testing of the wall thickness of metal components. The SONOWALL 60 reliably inspects e.g. pipes, tanks, machine and steel components as well as pressure vessels for signs of wear. It is also used in quality assurance and incoming goods inspection.



Technical Data	
Sound Velocity	2 000 m/s 7 000 m/s in steel
Measurement Range	3 mm 250 mm in steel with 2,25 MHz 1 mm 50 mm in steel with 5 MHz
Accuracy	± 0,1mm or ± 0.05 mm
Resolution	±0,1mm or ±0.05mm
Battery	2 × AA (replaceable), optional rechargeable batteries
Size	85 mm × 115 mm × 25 mm
Display	Illuminated LCD display
Weight	275 g
Ambient Temperature	-10°C +50°C
Storage Temperature	-10 °C +60 °C
Protection Class	Gauge: IP65, probe: IP67
Scope of Delivery	SONOWALL 60 gauge, protective silicone sleeve with adjustable neck strap, standard probe, probe cable (1.5m), accessory pouch containing couplant gel, spare membranes, membrane coupling oil, 15 mm (or 1") test block, batteries, operating manual and carrying case

Advantages

- → Reliably measures through coatings as well as rough and uneven surfaces
- → Deep coat mode for measurements on thick plastic coatings up to 20 mm
- → Short inspection times, lower inspection costs
- → High reproducibility
- → Automatic zero point adjustment
- → Automatic search unit recognition
- → For harsh operating conditions



Ultrasonic Probes

SW2-11 - 2MHz S5A - 5MHz

(Selection)

Contact and Support

SONOTEC GmbH Nauendorfer Str. 2 06112 Halle (Saale) Germany **49** (0)345 / 133 17-0

www.sonotec.eu

⊘ Certified according to ISO 9001